

**PERFORATED WHITE ONE-WAY PRIVACY**

Outside Application



**Description**

Standard perforated one-way vision privacy window film which looks white from the outside and blocks the view into buildings during the daytime. Allows excellent see-through for people inside the building with a black tint effect. For outside window application.



Colour

**White (outside view)  
Black tint (inside view)**



Surface type

**Standard Perforated**



Installation

**Outside Window Application**



Privacy characteristics

**DAY: Excellent (\*)**

**NIGHT: N/A**

**VIEW OUT: Excellent**



On window durability

**3 Years+**



Storage (22°C, 55% humidity)

**2 Years**



Environmental standard

**REACH compliant**

**Roll Sizes Available**

10metres (length) x 1370mm (width)

50metres (length) x 1370mm (width)

50metres (length) x 1520mm (width)

(\*) A low level of privacy will be given if there is more light on the inside than on the outside of the window, e.g. if the inside is illuminated at night.

**Technical Specification**

Face film	Warm white on black laminated polymeric PVC
Thickness	180micron +/- 10
Hole pattern	30% perforated; 1.5mm diameter micro holes
Adhesive	Transparent, semi-permanent
Protective release liner	Silicone coated paper
Min appl temp	4°C.

**Installation Recommendations**

For vertical installation on standard glass. Apply using a dry application method. Glass must be thoroughly cleaned beforehand with soap and water. Rinse and dry glass after cleaning.

Not to be applied to fresh paint or ink, polycarbonate, rubber, plastic moldings and certain PVCs. In case of doubt, please test prior to final application.

This product is not recommended for use around a sharp angle where there is a limited area either side of the angle.

The film must not touch the rubber window moulding. Not to be washed within 24 hours of application.

\* Not recommended for use on glass with coatings such as anti-reflective, self-cleaning and scratch-resistance

**Maintenance care**

Wash with soapy water. Gently wipe with lint cloth or soft bristled brush to remove grease and dirt. Take particular care not to damage the edges and corners. Wash off suds and leave to dry.

**Solar Properties**

Data calculated based on film applied to clear glass 3mm thick.

Visible light transmission	27%
Visible light reflection, exterior	58%
Visible light reflection, interior	11%
UV transmission	21%
Solar energy transmission	25%
Solar energy reflection	58%
Solar energy absorption (total)	17%
Glare reduction (relative %)	70%
g value	0.26
Shading coefficient (SC)	0.30

**Contact Information**

Contra Vision Supplies Ltd,  
Victoria House 19–21 Ack Lane East,  
Bramhall, Stockport, SK7 2BE,  
United Kingdom  
Tel. +44 161 439 9307  
Email: sales@contravision.com  
Web: www.contravision.com

This document is intended as a source of information, is given without guarantee, and does not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of the product for their specific intended purpose.